

Cordis **STORQ**[™]

Steerable Guidewires

Steerability and Torque,
experience the Control




Cordis **STORQ**TM

Steerable Guidewires

The **STORQ**TM Guidewire brings you a softer tip and sturdy support

Steerability and Torque, Experience the control

- Redesigned STORQ guidewire's atraumatic tip segment is softer and more flexible to guard against intimal damage or plaque disruption during device delivery and catheter exchange.
- Length of core taper has been modified to provide three different distal flexibilities - soft, supersoft, and standard - for accurate placement in diverse anatomy.
- Preshaped angled, modified J, and straight tip shapes provide physician with procedural flexibility.



Excellent Tip and Body Visualisation


- Radiopaque distal tip and radiolucent shaft permit clear fluoroscopic visualisation that allows precise placement.




Different Taper Lengths for Procedural Flexibility

If you want...	Then select...	Taper length
Firm support	Standard	10 cm
Multifunctional capability	Soft	13 cm
Maximum flexibility	SuperSoft	25 cm

PTFE and SLX
Guidewire Coatings



Torque Device



PTFE and SLX™ Coatings for Superb Lubricity

- PTFE (polytetrafluoroethylene) and SLX (silicone) coatings cover most of the guidewire, creating an exceptional lubricious surface for improved catheter tracking and guidewire movement.
 - Proximal segment is uncoated for secure attachment of torque device.
 - PTFE coating ends 10 cm from distal tip, while SLX coating continues to tip to facilitate crossing tight or tortuous lesions.
- PTFE and SLX coatings do not flake or peel even when the Storq guidewire is advanced through a needle lumen.

Excellent Support

- STORQ provides enhanced shaft support and stability for stent and balloon catheter delivery.
- STORQ maintains excellent torqueability and steerability for controlled access to target lesions.
- Design features:
 - Rigid, one-piece, stainless steel core for excellent torque response to prevent whipping.
 - Single outer coil that runs entire length of wire for more flexibility.



Cordis **STORQ**TM

Steerable Guidewires

Packaged five per box
Torque device included with each guidewire



Ordering information

Diameter (inch)	Tip Flexibility	Tip Shape	Length (cm)	Catalogue Number
.035	SuperSoft	Straight	180	503-256
.035	SuperSoft	Angled	180	503-256J
.035	Soft	Straight	180	503-356
.035	Soft	Angled	180	503-356J
.035	Soft	Modified J	180	503-356MJ
.035	Soft	Straight	300	503-356X
.035	Soft	Angled	300	503-356Y
.035	Soft	Modified J	300	503-356MY
.035	Standard	Straight	180	503-456
.035	Standard	Angled	180	503-456J
.035	Standard	Modified J	180	503-456MJ
.035	Standard	Straight	300	503-456X
.035	Standard	Angled	300	503-456Y
.035	Standard	Modified J	300	503-456MY

Also available with Helix-angled inner and outer quadrafilar coils and no PTFE coating

Important Information:

Prior to use, refer to the "Instructions for use" supplied with these devices for indications, contraindications, side effects, suggested procedure, warnings and precautions. As part of the Cordis policy of continuous product development we reserve the right to change product specifications without prior notification.